



OTSEN LED SPOTLIGHT MODULE

The OTSEN Siskalite LED Module is a high-performance lighting solution designed for precision and reliability. It features a premium BRIDGELUX chip paired with a Tridonic driver to ensure optimal efficiency, stability, and flicker-free operation. Engineered with an IP44 protection rating, the module is suitable for indoor environments where resistance to dust and moisture is essential. It is compatible with a range of frame fixtures, offering flexibility in installation and design. The Siskalite provides selectable beam angle options of 15°, 24°, and 38°, making it ideal for various lighting applications from accent to general illumination.

Application Areas

- Residential
- Hotels
- Offices
- Shops
- Kitchen & Bathrooms
- corridors

bridgelux[®]
Chip

TRIDONIC
DRIVER

IP
40

FlickerFree

110
lm /W

PF
0.95

PC
-22~50

50000
Hours
Lifespan

Anti Glare

ACBS-265V

UGR<19

5
YEARS
WARRANTY

Product Features

- Very clean appearance design, provide a nice look.
- High lumen efficiency reach up to 110Lm/W.
- Provide uniform light distribution ,the light is soft and comfortable .
- 220-265V input, PF>0.90, it's a flicker free product.
- TRIDONIC driver and Bridgelux chip
- 50,000H, 5 Years warranty .
- Flicker Free.
- UGR<19
- Beam angle 38°

Product & Information

Luminaire Details	Product Name	SISKALITE LED SPOTLIGHT
	Product Type	Spot Light
	Luminaire Type	COB
	IP Rating	IP40
	Source brand	Bridgelux
	Luminaire Efficacy	110lm/W
	Available CCT	3000K, 4000K & 6500K
	CRI	>95
	McAdamBinning	Step 3
	Body Material	Aluminium Die Cast
	Storage Temperature (Ts)	-22°C to 50°C
	Ambient Temperature (Ta)	-22°C to 50°C
	Humidity	RH 10-90 %

Product Details

Model	Power(W)	Colour Temperature	Luminous (LM)	Dimensions	Cutout Dimensions	Angle (Reflector)
OT-SP-8W-SL	8W	6500K,4000K, 3000K	110LM/W	Dia 50xH50mm	Ø 50	15° 24° 38°
OT-SP-10W-SL	10W	6500K,4000K, 3000K	1440LM	Dia 50xH50mm	Ø 50	15° 24° 38°
OT-SP-12W-SL	12W	6500K,4000K, 3000K	2160LM	Dia 50xH68mm	Ø 50	15° 24° 38°
OT-SP-15W-SL	15W	6500K,4000K, 3000K	2160LM	Dia 50xH68mm	Ø 50	15° 24° 38°

Suitable Frame





© 2023 OTSEN UK PVT. LTD. all rights reserved. OTSEN reserves the right to make changes in specifications and / or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.otsen.co.uk