







### OTSEN LEXO STADIUM FLOOD LIGHT

The OTSEN LEXO 1000W Stadium Flood Light delivers an impressive luminous efficacy of 160 lumens per watt, ensuring optimal brightness and energy efficiency. Built with a robust IP66-rated enclosure, it offers superior protection against dust and water, making it ideal for outdoor environments. Equipped with high-performance BRIDGELUX chips and a reliable Inventronics driver, this flood light guarantees excellent performance and longevity. Available in sleek gray or black finishes, the LEXO flood light combines durability and modern aesthetics, making it a perfect choice for stadiums and large outdoor areas.

## **Application Areas**

- Building
- Residential Area
- Commercial
- Pathway
- Parking Area
- Stadium
























### **Product Features**

- Very clean appearance design, provide a nice look.
- High lumen efficiency reach up to 160 Lm/W.
- Provide uniform light distribution, the light is soft and comfortable.
- Special spraying process, with very good anti-rust ability.
- Back-lit design makes no yellowing ,no darkness area even after years using .
- 100-240V input, PF>0.90, it's a flicker free product.
- 50,000H, 5 Years warranty.
- Flicker Free.
- Beam angle 120°


### **Product & Information**

Luminaire Details	Product Name	OTSEN LEXO LED STADIUM FLOOD LIGHT
	Product Type	LED FLOOD LIGHT
	Product code	OT-LX-FL-1000
	Luminaire Type	SMD
	IP Rating	IP66
Light source Details	Light Emission	Surface Emission
	Source brand	Bridgelux
	Luminaire Efficacy	160 lm/W
	Available CCT	3000K, 4000K & 6500K
	CRI	>80
	McAdamBinning	Step 5
Luminaire Housing	Body Material	Aluminium Die Cast
	Lens/Diffuser	Polycarbonate Lens
	Housing	SPCC with white spray painting
	Product Size	488x455x189 mm
Application Condition	Storage Temperature (Ts)	40°C to 50°C
	Ambient Temperature (Ta)	20°C to 50°C
	Humidity	RH 10-90 %

# **Light Distribution Curve**



## **Product Drawing**



L: 827mm W: 452mm

H: 165mm



© 2023 OTSEN UK PVT. LTD. all rights reserved. OTSEN reserves the right to make changes in specifications and / or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.