

LED GARDEN POLE LIGHT



OTSEN LED GARDEN POLE LIGHT

The OTSEN Garden Light offers versatile lighting solutions with both Single Head and Double Head, providing flexible illumination for various outdoor spaces. The Single Head option delivers over 140 lumens per watt and is equipped with high-quality LEDs, which offers enhanced coverage for larger areas. Both options come with a choice of premium drivers, including the reliable MEANWELL driver, as well as alternatives such as the PHILIPS driver, CREE chip, and SOSEN driver. Designed with an IP67 rating for excellent weather resistance, these lights are suitable for parks, gardens, and other outdoor environments. Available in black, silver, and grey color options, they also come in height choices of 3 meters, 4 meters, 5 meters, and 6 meters, ensuring the perfect solution for any lighting need.

Application Areas

- Walkways
- Parks / Gardens
- Car parking
- Prestigious
- Retail
- Amenity



Product Features

- Main body is made of Die casting aluminum alloy.
- The diffuser is a frosted anti-UV glass for high efficiency and vandal resistance.
- Installation tube diameter:76mm.
- Lumileds 3030 led chip and Meanwell driver as regular, Sosen, Philips driver options.
- Easy access to LED and driver,with 1-10V,Dali,PWM dimmable options.
- 2700-6500K color temperature options.
- Tamper proof fixings for increased vandal resistance.
- Anti-UV electrostatic powder spraying, regular color : Black, Silver, RAL7043, RAL7016 & Grey.
- IP67 rating water and rust proof protection.
- IK09 rating housing protection.
- Warranty is 6 years.


Product & Information

Product Data	Model Number	OTG-LED-067
	Model Name	OTSEN LED GARDEN POLE LIGHT
	Product Colour	Black, Silver, RAL7043, RAL7016 & Grey
	Body Material	Heavy-Duty Aluminium
	Wattage	30W, 40W, 50W, 65W, 75W
	Product Style	Garden Light
Technical Data	Input Wattage	AC85-265V, AC/50-60Hz
	Lighting Source	Cree LED, Lumileds
	Luminous	140 Lumen/Watt
	Color Temperature	6500K, 5000K , 4000K, 3000K
	Color Rendering Index	Ra>80
	Safety Class	Class I
	Power Factor	0.95
	Type of Protection	IP 67
	Warranty	6 Years
	Life span	50000 hrs.
	IK Rating	IK10



Wattage and Lumens

Item No.	LED	Lumens	Wattage	CCT	CRI
OTG-LED-067-30W	Lumileds 3030	4200LM	30W	2700-6500K	≥80
OTG-LED-067-40W	Lumileds 3030	5600LM	40W	2700-6500K	≥80
OTG-LED-067-50W	Lumileds 3030	7000LM	50W	2700-6500K	≥80
OTG-LED-067-65W	Lumileds 3030	9100LM	65W	2700-6500K	≥80
OTG-LED-067-75W	Lumileds 3030	10500LM	75W	2700-6500K	≥80

Product Structural Design



Light Distribution





© 2023 OTSEN UK PVT. LTD. all rights reserved. OTSEN reserves the right to make changes in specifications and / or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.otsen.co.uk