





## WINDY SERIES

# **LED** WINDY BULKHEAD

#### OTSEN WINDY BULKHEAD

The OTSEN WINDY BULKHEAD LIGHT is a robust and energy-efficient lighting solution designed for indoor environments. With an IP44 rating, it is dust-tight and resistant to water splashes, ensuring reliable performance even in demanding conditions. Consuming just 15 watts of power (customizable), it delivers an impressive 110 lumens per watt, offering a perfect balance between brightness and energy efficiency. The light boasts a power factor greater than 0.90, minimizing energy losses, and a Color Rendering Index (CRI) above 80, ensuring accurate and vibrant color representation. Ideal for corridors, stairwells, utility rooms, and general-purpose indoor applications.

#### **Application Areas**

- Residential
- Hotels
- Hospital
- Commercial
- Offices
- Schools





2023, OTSEN UK, All Rights reserved. OTSEN UK TM REG.No. : UK00003940603 page 1 of 6

bridgelux. LiFud



### **Product Features**

- Very clean appearance design, provide a nice look.
- High lumen efficiency reach up to 110Lm/W.
- Provide uniform light distribution ,the light is soft and comfortable .
- IP44 high protection level.
- Opal Diffuser
- 220-240V input, PF>0.90, it's a flicker free product.
- Lifud driver and Bridgelux chip
- 50,000H, 5 Years warranty .
- Flicker Free.
- Beam angle 120°

#### Product & Information

| Luminaire<br>Details     | Product Name             | OTSEN WINDY BULKHEAD LIGHT          |
|--------------------------|--------------------------|-------------------------------------|
|                          | Product Type             | BULKHEAD                            |
|                          | Product code             | OT-WYBH                             |
|                          | Luminaire Type           | SMD                                 |
|                          | Wattage                  | 12W, 18W, 22W                       |
| Light source<br>Details  | IP Rating                | IP44                                |
|                          | Light Emission           | Surface Emission                    |
|                          | Source brand             | Bridgelux                           |
|                          | Luminaire Efficacy       | 110lm/W                             |
|                          | Available CCT            | 3000K, 4000K, 6500K & CCT changable |
|                          | CRI                      | >80                                 |
| Luminaire<br>Housing     | McAdamBinning            | Step 3                              |
|                          | Body Material            | Aluminium                           |
|                          | Lens/Diffuser            | Polycarbonate Diffuser              |
|                          | Housing                  | Aluminium                           |
|                          | Diffuser                 | Opal Diffuser                       |
|                          | Storage Temperature (Ts) | -10°C to 60°C                       |
|                          | Ambient Temperature (Ta) | -10°C to 60°C                       |
|                          | Humidity                 | RH 10-90 %                          |
| Application<br>Condition | Available Options        | Microwave Sensor                    |
|                          |                          | Emergency Light                     |
|                          |                          | Dalli, Dimmable                     |
|                          |                          |                                     |



## **Product Detail**





Wall mounted



**Product Lighting Diagram** 





© 2023 OTSEN UK PVT. LTD. all rights reserved. OTSEN reserves the right to make changes in specifications and / or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.